



- NOTES:
- 1) HYDRO @ 260 PSIG. MIN.
  - 2) CRN SASKATCHEWAN
  - 3) IMPACT TESTED? NO UG-20(f)
  - 4) WELD SIZE NPT UW-16(f)(5)
  - 5) MANWAY RING EDGES MUST BE ROUNDED PER: UG-76(c)

SHELL / HEADS		.166" SA-414-G 2:1 S.E.	
		(.164"MIN.) JOGGLED-GREEN STRIPE	
		.200" SA-455	
M.A.W.P.	200 PSIG. @ 200 °F		
M.D.M.T.	-20 °F @ 200 PSIG.		
ASME SECTION VIII DIV. 1, 2013			
X-RAY:	RT-NO		
GALLONS:	200	WT. 488	LBS.
SERIAL NO.			
N.B.			
0-30-VA-200-R		REV. 12-26-13	
FOR: HANSON STANDARD		DATE: 5-23-94	
VERT. AIR TANK			
SURFACE AREA = 50.2 SQ. FT.			
INSIDE: EPOXY LINED			
OUTSIDE: PRIME			
CAD-"B" SIZE UNDER "0"-SERIES			
BY: E.S.	SCALE: 1"=12"		
<b>ROY E. HANSON JR. MFG.</b>			
1600 E. WASHINGTON BLVD.			
LOS ANGELES, CA 90021			