



NOTE: 1) 2) DRAIN FOR HORIZONTAL MOUNT ADDED AFTER SERIAL #423,136  
 HYDRO @ 260 PSIG. MIN.

SHELL / HEADS		.245" SA-455 2:1 S.E.	
M.A.W.P. 200 PSIG. @ 400 °F		JOGGLE	
M.D.M.T. -20 °F @ 200 PSIG.		.250" SA-455	
ASME. SECTION VIII DIV. 1, 2007 ADD 2009		M.A.W.P. 200 PSIG. @ 400 °F	
X-RAY: RT-4 SPOT L.S. ONLY		M.D.M.T. -20 °F @ 200 PSIG.	
GALLONS: 660 WT. 1477 LBS.		ASME. SECTION VIII DIV. 1, 2007 ADD 2009	
SERIAL NO.		X-RAY: RT-4 SPOT L.S. ONLY	
N.B.		GALLONS: 660 WT. 1477 LBS.	
42-VA-660-R		SERIAL NO.	
FOR: HANSON STANDARD		N.B.	
VERT. AIR TANK		42-VA-660-R	
INSIDE: UNPAINTED		FOR: HANSON STANDARD	
OUTSIDE: PRIME		VERT. AIR TANK	
CAD "B" SIZE UNDER "STD"-SERIES		INSIDE: UNPAINTED	
BY: E.S.		OUTSIDE: PRIME	
SCALE: 3/4"=12"		CAD "B" SIZE UNDER "STD"-SERIES	
ROY E. HANSON JR. MFG.		BY: E.S.	
1600 E. WASHINGTON BLVD.		SCALE: 3/4"=12"	
LOS ANGELES, CA 90021		ROY E. HANSON JR. MFG.	
		1600 E. WASHINGTON BLVD.	
		LOS ANGELES, CA 90021	