



2" B W/C.I. PLUG  
INSP. OPENING  
(2) PLC'S

4"-150# R.F.S.O.  
FLG. W/SCH 40  
SA-106-B SMLS.  
PIPE x 7 1/16" LG.  
(2) PLC'S

(4) 3" x 3" x 3/16" THK.  
x 22 15/16" LG. ANGLE LEGS

(4) 4" x 4" x 5/16" THK.  
PAD W/7/8" Ø HOLE  
FOR 5/8" Ø x 8" LG BOLTS  
GRADE 5 OR BETTER  
6" EMBEDMENT

NOTE: 1) HYDRO @ 163 PSIG. MIN.

SHELL / HEADS	
.182" SA-455	2:1 S.E.
JOGGLE	
.164" SA-414-G	
M.A.W.P.	125 PSIG. @ 210 °F
M.D.M.T.	-20 °F @ 125 PSIG.
ASME. SECTION VIII	DIV. 1, 2007 ADD 2009
X-RAY:	RT-NO
GALLONS:	325 WT. 619 LBS.
SERIAL NO.	
N.B.	

<b>WM-876-B</b>	
FOR: -	REV: -
VERT. WATER (BUFFER) TANK	DATE: 1-21-10
SURFACE AREA = 68.0 SQ. FT.	
UW-21 (b)	
INSIDE: UNPAINTED	
OUTSIDE: PRIME	
LEG ZONE: 4-5 KM.	
BY: J.G./R.L.	SCALE: 1"=12"
<b>ROY E. HANSON JR. MFG.</b>	
1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021	

