



NOTE: 1) HYDRO @ 195 PSIG. MIN.

HEADS		SHELL	
.135" SA-414-G 2:1 S.E.		.136" SA-414-G	
JOGGLE			
M.A.W.P. 150 PSIG. @ 347 °F		M.A.W.P. 150 PSIG. @ 347 °F	
M.D.M.T. -20 °F @ 150 PSIG.		M.D.M.T. -20 °F @ 150 PSIG.	
ASME SECTION VIII DIV. 1, 2010 ADD 2010		ASME SECTION VIII DIV. 1, 2010 ADD 2010	
X-RAY: RT-NO		X-RAY: RT-NO	
GALLONS: 30 WT. 93 LBS.		GALLONS: 30 WT. 93 LBS.	
SERIAL NO.		SERIAL NO.	
N.B.		N.B.	
X-30		X-30	
FOR: HANSON STANDARD		FOR: HANSON STANDARD	
HORIZ. EXPANSION TANK		HORIZ. EXPANSION TANK	
SURFACE AREA = 15.3 SQ. FT.		SURFACE AREA = 15.3 SQ. FT.	
INSIDE: UNPAINTED		INSIDE: UNPAINTED	
(GALVANIZING OPTIONAL)		(GALVANIZING OPTIONAL)	
OUTSIDE: PRIME		OUTSIDE: PRIME	
BY: E.S.		BY: E.S.	
SCALE: 1/8"=1"		SCALE: 1/8"=1"	
ROY E. HANSON JR. MFG.		ROY E. HANSON JR. MFG.	
1600 E. WASHINGTON BLVD.		1600 E. WASHINGTON BLVD.	
LOS ANGELES, CA 90021		LOS ANGELES, CA 90021	
REV. 8-24-11		REV. 8-24-11	
DATE: 1-3-79		DATE: 1-3-79	