



2"R W/STL. PLUG
INSP. OPENING
(2) PLC'S

SUPT'S PER:
MA-102-1-B
(18" TANK SUPT'S)

5/8"Ø HOLE
(2) PLC'S

NOTE: 1) HYDRO @ 392 PSIG. MIN.

HEADS	.165" SA-414-G 2:1 S.E.	20-HD-80-W	REV. 4-19-07
	JOGGLE - .199" OFFSET		DATE: 4-26-04
SHELL		FOR: HANSON STANDARD	
		HORIZ. AIR TANK	
	.165" SA-414-G		
		INSIDE: UNPAINTED	
	M.A.W.P. 300 PSIG. @ 400 °F		
	M.D.M.T. -20 °F @ 300 PSIG.	OUTSIDE: PRIME	
	ASME. SECTION VIII DIV. 1, 2004 ADD 2006	CAD-"B" SIZED UNDER "STD"-SERIES	
	X-RAY: RT-4 SPOT L.S. ONLY	BY: J.G.	SCALE: 1"=12"
	GALLONS: 80	WT. 233 LBS.	ROY E. HANSON JR. MFG. 1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021
	SERIAL NO.		
	N.B.		