



NOTE: 1) HYDRO @ 715 PSIG. MIN.
 2) ALL CPLG'S ARE 3000# HALF, EXCEPT 1/4"-3000# FULL CPLG.
 3) PRE HEAT BEFORE WELDING TO 150°F

SHELL / HEADS		.500" SA-516-70 2:1 S.E. (.472"MIN.) - BEVEL	30-HK-240-W	REV. 6-6-11
HOT FORMING NOT REQUIRED		UCS 79(d)	FOR: HANSON STANDARD	DATE: 6-25-87
.500" SA-516-70			HORIZ. AIR TANK	
			SURFACE AREA = 62.3 SQ. FT.	
INSIDE: UNPAINTED				
M.A.W.P. 550 PSIG. @ 400 °F			OUTSIDE: PRIME	
M.D.M.T. -20 °F @ 550 PSIG.			CAD-"B" SIZE UNDER "STD"-SERIES	
ASME SECTION VIII DIV. 1, 2010 ADD 2010			BY: J.G. SCALE: 1"=12"	
X-RAY: RT-4 SPOT L.S. ONLY			ROY E. HANSON JR. MFG.	
GALLONS: 240 WT. 1393 LBS.			1600 E. WASHINGTON BLVD.	
SERIAL NO.			LOS ANGELES, CA 90021	

VIEW W/O OUT SUPT'S