



VIEW W/O SUPPORTS

NOTE: 1) HYDRO @ 717 PSIG. MIN.
 2) PRE-HEAT ALL WELDS TO 150°F.

| | | | |
|---|--------------------------|---|----------------|
| HEADS | .500" SA-516-70 2:1 S.E. | 36-HK-500-W | REV. 4-5-07 |
| | (.485" MIN.) TRIM | | DATE: 11-18-02 |
| SHELL | .500" SA-516-70 | FOR: HANSON STANDARD HORIZ. AIR TANK | |
| | | INSIDE: UNPAINTED | |
| M.A.W.P. 550 PSIG. @ 400 °F | | OUTSIDE: PRIME | |
| M.D.M.T. -20 °F @ 550 PSIG. | | CAD-"B" SIZE UNDER "STD"-SERIES | |
| ASME SECTION VIII DIV. 1, 2004 ADD 2006 | | BY: E.S. SCALE: 3/4"=12" | |
| X-RAY: RT-2, 100% L.S. & SPOT G.S. | | ROY E. HANSON JR. MFG. | |
| GALLONS: 500 WT. 2175 LBS. | | 1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021 | |
| SERIAL NO. | | | |
| N.B. | | | |