



3/4"  $\phi$  SOLAR L. LUG (2) PLC'S.

5.18 FC TYP.

5" STICK OUT

11" x 15" H. HOLE W/ 1" x 3" LG. GR. 70 RING

1/4"  $\phi$  5.2 FC

3/4" - 3000# FULL CPLG.

2 1/2" - 2000# EXT. CPLG. W/ NO PILOT (2) PLC'S.

NOTE: 1) SHIP LOOSE W/ (2) 1 5/16" x 48" LG. FLEX. MAG. ANODES.  
 2) HYDRO @ 240 PSIG. MIN.  
 3) SHELL: 4-22-04 PROOF TEST.

SHELL / HEADS		.250" SA-414-G 2:1 S.E.	
JOGGLE - .198 OFFSET		GS-48-712-H	
.200" SA-455		REV. 10-31-11	
M.A.W.P. 160 PSIG. @ 210 °F		DATE: 5-15-90	
ASME SECTION IV 2010 ADD. 2010		FOR: HANSON STANDARD	
X-RAY: RT-NO/H.L.W.		HORIZ. HOT WATER TANK	
GALLONS: 712 WT. 1159 LBS.		SURFACE AREA = 113.0 SQ. FT.	
SERIAL NO.		INSIDE: GLASS LINED	
		OUTSIDE: PRIME	
		CAD-"B" UNDER "STD"-SERIES	
		BY: J.G. SCALE: 3/4"=12"	
		<b>ROY E. HANSON JR. MFG.</b>	
		1600 E. WASHINGTON BLVD.	
		LOS ANGELES, CA 90021	

END VIEW W/O SUPPORTS