



NOTE: 1) SHIP LOOSE W/(2) 1 5/16" x 84" LG. FLEX. MAG. ANODES.
 2) HYDRO @ 188 PSIG. MIN. TO 197 PSIG. MAX.
 3) 5-6-04 PROOF TEST.
 5) 1 1/2"-3000# FULL CPLG. ON TOP-304 S.S.

SHELL / HEADS	.250" SA-455 2:1 S.E.	GS-60-1450-V	REV. 1-15-08
	.218" SA-455		DATE: 6-14-90
M.A.W.P.	125 PSIG. @ 210 °F	FOR: HANSON STANDARD	
ASME. SECTION	IV 2007 ADD. 2007	VERT. HOT WATER TANK.	
X-RAY:	RT-NO / H.L.W.	SURFACE AREA = 185.0 SQ. FT.	
GALLONS:	1450	INSIDE: GLASS LINED	
SERIAL NO.		OUTSIDE: PRIME	
N.B.		LEG-ZONE 4-15 KM.	
		CAD-"B" UNDER "STD"-SERIES	
		BY: J.G.	SCALE: 1/2"=12"
		ROY E. HANSON JR. MFG.	
		1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021	