



NOTE: 1) 10-1-04 PROOF TEST.
 2) SHIP LOOSE W/(2) 1 5/16" x 96" LG. FLEX. MAG. ANODES.
 3) HYDRO @ 240 PSIG.

SHELL / HEADS		M.A.W.P. 160 PSIG. @ 210 °F		ASME SECTION IV 2010 ADD 2010		X-RAY: RT-NO / H.L.W		GALLONS: 1650		WT. 2469 LBS.		SERIAL NO.		N.B.	
BTM.	.289" SA-455	2:1	S.E.	TOP	.289" SA-455	2:1	S.E.								
								(.254" MIN.)							
								.250" SA-455							
GS-64-1650-V															
FOR: HANSON STANDARD												REV: 12-14-11		DATE: 6-14-90	
VERT. HOT WATER TANK												SCALE: 1/2"=12"		BY: J.G.	
SURFACE AREA = 197.2 SQ. FT.												LEG-ZONE 4-15 KM.		CAD "B" SIZE UNDER "STD"-SERIES	
INSIDE: GLASS LINED												ROY E. HANSON JR. MFG.		1600 E. WASHINGTON BLVD.	
OUTSIDE: PRIME												LOS ANGELES, CA 90021			

(4) 4" x 4" x 1/2" x 27 15/16" LG. ANGLE LEG
 (4) 6" x 6" x 5/8" THK. PAD W/ 1" Ø HOLE FOR 3/4" Ø x 8" LG. BOLTS GRADE 5 OR BETTER 6" EMBEDMENT