



VIEW W/OUT SUPPT'S

- NOTE. 1) HYDRO @ 188 PSIG. MIN. TO 197 PSIG. MAX.  
 2) SHIP LOOSE W/(3) 1 5/16" x 72" LG. FLEX. MAG. ANODES.  
 3) SHELL & LEFT HEAD - 8/26/04 PROOF TEST.

SHELL / HEADS		LEFT - .250" SA-455 2:1 S.E. (.220" MIN.)	RIGHT - .317" SA-455 2:1 S.E. (.279" MIN.)	.252" SA-455
M.A.W.P.	125 PSIG. @	210 °F		
ASME. SECTION	IV	2007 ADD	2009	
X-RAY:	RT-NO/H.L.W.			
GALLONS:	2150	WT. 3223	LBS.	
SERIAL NO.				
N.B.				
FOR:	WM-856-B			
HORIZ. HOT WATER TANK.	REV. 3-4-10			
SURFACE AREA = 232.0 SQ.FT.	DATE: 12-7-09			
INSIDE: GLASS LINED				
OUTSIDE: S. BLAST, INORGANIC				
ZINC PRIME				
BY: J.G./C.J.	SCALE: 1/2"=12"			
<b>ROY E. HANSON JR. MFG.</b>				
1600 E. WASHINGTON BLVD.				
LOS ANGELES, CA 90021				