



NOTE. 1) HYDRO @ 188 PSIG. MIN. TO 197 PSIG. MAX.

2) SHIP LOOSE W/ (3) 1 5/16" x 60" LG. FLEX. MAG. ANODES.

3) ALL FNPT'S SA-182-304 S.S. EX. 1 1/4" FOR ANODE-C.S.

4) ALL PIPES SA-312-304 E.R.W. - USE 2" HALF CPLG. FOR THREAD PROTECTION.

5) 8-26-04 PROOF TEST.

6) TAG: 11TH ST.

STYLE "A" SADDLE W/ WELD ON CLIPS PER. WJ-993-B-1A

SHELL / HEADS		.219" MIN. SA-455 2:1 S.E.	
M.A.W.P.		125	PSIG. @ 210 °F
ASME SECTION IV		2010 ADD 2010	
X-RAY:		RT-NO / H.L.W.	
GALLONS:		1950	WT. 3025 LBS.
SERIAL NO.		N.B.	
FOR:		WN-302-B	
HORIZ. HOT WATER TANK		REV.	8-5-11
SURFACE AREA = 217.5 SQ. FT.		DATE:	7-25-11
INSIDE: GLASS LINED			
OUTSIDE: S. BLAST, PRIME			
BY: E.S. / C.J.		SCALE: 1/2"=12"	
ROY E. HANSON JR. MFG.		1600 E. WASHINGTON BLVD.	
		LOS ANGELES, CA 90021	