



304 S.S. -
1/4" THK. CLIPS PER
MA-395-B (4) PLC'S.
W/ 9/16" Ø HOLE ON
17 1/8" B.C.; WELD
OUTSIDE VERT. EDGE
OF CLIP ONLY

NOTE: 1) HYDRO @ 520 PSIG. MIN.
2) ALL FNPT'S SA-182-304 S.S.
3) UHA-51(e)(2)(d). NO IMPACT TESTING.

SHELL / HEADS		.1875" SA-240-304 2:1 S.E. (.187" MIN.)
M.A.W.P.	400 PSIG. @ 200 °F	
M.D.M.T.	-155 °F @ 400 PSIG.	
ASME SECTION VIII	DIV. 1, 2013	
X-RAY:	RT-NO	
GALLONS:	30	WT. 165 LBS.
SERIAL NO.		
N.B.		
16-VJ-30-R		REV.
304 S.S.		DATE: 12-13-13
FOR: HANSON STANDARD		
VERT. AIR TANK		
SURFACE AREA = 14.7 SQ. FT.		
INSIDE: PASSIVATE		
OUTSIDE: BEAD BLAST & PASSIVATE		
CAD "B" SIZE UNDER STD. SERIES		
BY: E.S.		SCALE: 1/8"=1"
ROY E. HANSON JR. MFG.		
1600 E. WASHINGTON BLVD. LOS ANGELES, CA 90021		