



VIEW W/O SUPPORTS

NOTE: 1) HYDRO TEST @ 195 PSIG. MIN.

SHELL / HEADS		.245" SA-455 2:1 S.E.	
JOGGLE			
.205" SA-414-G			
M.A.W.P.	150 PSIG. @ 400 °F		
M.D.M.T.	-20 °F @ 150 PSIG.		
ASME SECTION VIII DIV. 1, 2013			
X-RAY: RT-4 SPOT L.S. ONLY			
GALLONS: 1060	WT. 1770 LBS.		
SERIAL NO.			
N.B.			
48-HP-1060-W		REV. 3-12-14	
FOR: HANSON STANDARD		DATE: 3-14-94	
HORIZ. AIR TANK			
SURFACE AREA = 160.4 SQ. FT.			
LW-21(b)			
INSIDE: UNPAINTED			
OUTSIDE: PRIME			
CAD-"B" SIZE UNDER "STD"-SERIES			
BY: E.S.	SCALE: 3/4"=12"		
ROY E. HANSON JR. MFG.			
1600 E. WASHINGTON BLVD.			
LOS ANGELES, CA 90021			

6"-150# R.F.S.O.
 FLG. W/ SCH. 80
 SA-106-B
 PIPE x 7 5/8"LG.
 (2) PLC'S.

SUPPORTS PER:
 MA-102-6C